

DATE TEHNICE

6 poli

1000 rpm

Putere		Model	Turatie	Curent Nominal	Curent Pornire	Cuplu Nominal	Cuplu Pornire	Cuplu Maxim	Moment Inertie	Greutate
kW	CP		rpm	In (A) 400V 50Hz	Ip/In	Mn	Mp/Mn	Mmax/Mn	J (Kgm ²)	m (Kg)
0.09	0.16	63A-6	840	0.51	3.5	1.02	2	2	0.0003	4.2
0.12	0.16	63B-6	850	0.62	3.5	1.35	2	2	0.0005	4.8
0.18	0.25	71A-6	880	0.7	4	1.95	1.6	1.7	0.0008	6
0.25	0.34	71B-6	900	0.87	4	2.65	2.1	2.2	0.0010	6.5
0.37	0.5	71B-6	890	1.27	4	3.97	2	2.1	0.0011	7.2
0.37	0.5	80A-6	900	1.23	4	3.93	1.9	1.9	0.0015	8.2
0.55	0.75	80B-6	900	1.65	4	5.84	2	2.3	0.0023	9.9
0.75	1	80B-6	900	2.21	4	7.96	2	2.3	0.0029	11.3
0.75	1	90S-6	920	2.18	5.5	7.79	2.2	2.2	0.0038	11.7
1.1	1.5	90L-6	925	3.02	5.5	11.36	2.2	2.2	0.0047	15.1
1.5	2	100L-6	945	3.85	6	15.17	2.2	2.2	0.0073	19.1
2.2	3	112M-6	955	5.36	6	22.01	2.2	2.2	0.0130	25.4
3	4	132S-6	960	7.21	6.5	29.86	2	2	0.0284	36.1
4	5.5	132MA-6	960	9.44	6.5	39.81	2	2	0.0351	45
5.5	7.5	132MB-6	960	12.42	6.5	54.74	2	2	0.0461	55.5
7.5	10	132MB-6	960	16.54	6.5	74.65	2	2	0.0564	60
7.5	10	160M-6	970	16.2	5.6	73.9	2	2.6	0.0880	103
11	15	160L-6	970	23.2	5.8	108.3	2.1	2.4	0.1160	121
15	20	180L-6	970	30.1	5.7	147.7	2	2.4	0.2070	173

18.5	25		200LA-6	970	36.6	6.7	182.2	2.2	2.8	0.3150	221
22	30		200LB-6	970	42.5	6.6	216.7	2.3	2.9	0.3600	236