

DATE TEHNICE

4 poli

1500 rpm

Putere		Model		Turatie	Curent Nominal	Curent Pornire	Cuplu Nominal	Cuplu Pornire	Cuplu Maxim	Moment Inertie	Greutate
kW	CP			rpm	In (A) 400V 50Hz	Ip/In	Mn	Mp/Mn	Mmax/Mn	J (Kgm ²)	m (Kg)
0.06	0.09		56A4	1320	0.3	6	0.43	2.3	2.4	0.0002	3
0.09	0.12		56B4	1320	0.43	6	0.65	2.3	2.4	0.0002	3.3
0.12	0.16		56B4	1320	0.53	6	0.87	2.2	2.4	0.0002	3.5
0.12	0.16		63A-4	1350	0.47	6	0.85	2.2	2.4	0.0003	3.9
0.18	0.25		63B-4	1350	0.68	6	1.27	2.2	2.4	0.0003	4.3
0.25	0.34		63B-4	1350	0.91	6	1.77	2.2	2.4	0.0004	4.8
0.25	0.34		71A-4	1350	0.84	6	1.77	2.2	2.4	0.0005	5.4
0.37	0.5		71B-4	1370	1.11	6	2.58	2.2	2.4	0.0008	6.2
0.55	0.75		71B-4	1380	1.6	6	3.81	2.2	2.4	0.0009	7.3
0.55	0.75		80A-4	1370	1.58	6	3.84	2.2	2.4	0.0013	9
0.75	1		80B-4	1380	1.93	6	5.19	2.2	2.4	0.0015	10
1.1	1.5		80B-4	1390	2.67	6	7.56	2.2	2.4	0.0018	12.3
1.1	1.5		90S-4	1400	2.64	6	7.51	2.2	2.4	0.0022	12.1
1.5	2		90L-4	1400	3.45	6	10.24	2.2	2.4	0.0028	14.6
2.2	3		90L-4	1400	4.9	7	15.02	2.2	2.4	0.0037	18.3
2.2	3		100LA-4	1420	4.84	7	14.8	2.2	2.3	0.0058	21
3	4		100LB-4	1420	6.47	7	20.19	2.2	2.3	0.0073	24.7
4	5.5		100LB-4	1430	8.36	7	26.73	2.2	2.3	0.0092	29
4	5.5		112M-4	1430	8.26	7	26.73	2.2	2.2	0.0107	30.5

5.5	7.5		112M-4	1440	11.16	7	36.49	2.2	2.2	0.0130	34.8
5.5	7.5		132S-4	1450	11.03	7	36.24	2.2	2.2	0.0230	40.4
7.5	10		132M-4	1450	14.64	7	49.42	2.2	2.2	0.0304	49.6
9.2	12.5		132MA-4	1460	17.85	7.5	60.21	2.2	2.2	0.0359	56.5
11	15		132MB-4	1460	20.88	7.5	71.99	2.2	2.2	0.0410	64
11	15		160M-4	1460	21.3	6.9	72	2.3	2.9	0.0750	109
15	20		160L-4	1460	28.5	6.8	98.2	2.3	2.9	0.0920	130
18.5	25		160L-4	1455	36.3	6.8	120	2.3	2.9	0.1390	137
18.5	25		180M-4	1470	34.4	6.4	120.2	2.3	2.9	0.1390	165
22	30		180L-4	1470	40.7	6.9	143	2.3	2.9	0.1580	180
30	40		180L-4	1475	52.8	6.9	195	2.3	2.9	0.2620	137
30	40		200L-4	1470	54.7	6.8	195	2.4	2.9	0.2620	240